

Allowable Uniform Load (lbs.) – 2000psi

PowersSPAN Standard Lintels are Stronger Than Mansonry Lintel, and Easier to Install!

Lintel Height		16"			24"			32"			40"			48"		
Reinforcement		2#4	2#5	2#6	2#4	2#5	2#6	2#4	2#5	2#6	2#4	2#5	2#6	2#4	2#5	2#6
Type of Lintel	Opening Span															
Masonry Lintel	2'-0"	3098	3020	2953												
Powers Steel	2'-0"	6881	6881	6881												
ML	2'-8"	2321	2262	2212												
PS	2'-8"	5161	5161	5161												
ML	3'-4"	1851	1841	1773												
PS	3'-4"	4129	4129	4129												
ML	4'-0"	1549	1510	1475	2850	2592	2541									
PS	4'-0"	3441	3441	3441	4777	4777	4777									
ML	4'-8"	1327	1292	1255	2270	2220	2177									
PS	4'-8"	2949	2949	2949	4095	4095	4095									
ML	5'-4"	1163	1133	1108	1989	1945	1907									
PS	5'-4"	2580	2580	2580	3583	3583	3583									
ML	6'-0"	1033	1007	984	1767	1728	1894	2510	2461	2418	3259	3201	3149			
PS	6'-0"	2294	2294	2294	3185	3185	3185	4076	4076	4076	4967	4967	4967			
ML	6'-8"	929	905	885	1539	1555	1524	2258	2214	2175	2932	2880	2833			
PS	6'-8"	2064	2064	2064	2866	2866	2866	3668	3668	3668	4470	4470	4470			
ML	7'-4"	845	824	806	1446	1415	1387	2055	2015	1979	2685	2821	2578			
PS	7'-4"	1877	1877	1877	2606	2606	2606	3335	3335	3335	4064	4064	4064			
ML	8'-0"	775	755	738	1325	1298	1271	1862	1846	1813	2444	2401	2382	3009	2960	2915
PS	8'-0"	1720	1720	1720	2389	2389	2389	3075	3075	3075	3725	3725	3725	4393	4393	4393
ML	8'-8"	715	697	681	1228	1196	1172	1737	1703	1675	2255	2216	2179	2777	2731	2590
PS	8'-8"	1588	1588	1588	2205	2205	2205	2822	2822	2822	3439	3439	3439	4055	4055	4055
ML	9'-4"	618	647	633	1058	1111	1090	1501	1583	1555	1949	2059	2025	2399	2538	2499
PS	9'-4"	1475	1475	1475	2047	2047	2047	2620	2620	2620	3193	3193	3193	3766	3766	3766
ML	10'-0"	558	604	591	919	1037	1017	1306	1477	1451	1896	1921	1890	2088	2368	2532
PS	10'-0"	1376	1376	1376	1911	1911	1911	2445	2445	2445	2980	2980	2980	3515	3515	3515
ML	12'-0"	373	474	492	638	864	847	907	1231	1209	1178	1601	1575	1450	1973	1943
PS	12'-0"	1147	1147	1147	1592	1592	1592	2038	2038	2038	2483	2483	2483	2929	2929	2929
ML	14'-0"	274	348	384	469	711	726	867	1013	1086	855	1318	1350	1055	1624	1668
PS	14'-0"	983	983	983	1365	1365	1365	1747	1747	1747	2129	2129	2129	2511	2511	2511
ML	16'-0"	210	266	294	359	545	635	510	776	907	683	1009	1181	816	1244	1457
PS	16'-0"	860	860	860	1194	1194	1194	1523	1523	1523	1863	1863	1863	2197	2197	2197
ML	18'-0"	166	211	232	284	430	557	403	613	806	524	797	1050	645	983	1295
PS	18'-0"	765	765	765	1062	1062	1062	1359	1359	1359	1656	1656	1656	1953	1953	1953
ML	20'-0"	134	171	188	230	349	451	327	496	692	424	646	901	622	798	1113
PS	20'-0"	643	643	643	955	955	955	1223	1223	1223	1490	1490	1490	1757	1757	1757